



Bobcat®

GO WHERE THE WORK IS. 1000 PLATFORM SUB-COMPACT TRACTORS

Tough jobs fit in the smallest spaces. That's where the maneuverability of Bobcat® sub-compact tractors really shines. These small but powerful machines bring excellent capabilities to a wide variety of light-duty tasks, inside and around barns and sheds or trees and landscaping. From mowing small clearings and maintaining driveways in every season to doing loader work and other light-duty tasks, your Bobcat 1000 platform tractor earns its keep all year.



HYDROSTATIC TRANSMISSION (2-RANGE HST)

The hydrostatic transmission uses hydraulic pressure to change speed, operating similar to a vehicle. You'll only need to stop moving if you want to change your range. This is a good transmission choice if you're doing frequent front-end loader work, mowing or clearing brush as you maneuver through wooded areas. Its ease of operation also makes it a good choice for novice drivers. Forward and reverse are controlled by foot pedals.

TIGHT TURNING RADIUS

Maximum maneuverability is the key to effective mowing, tilling and more. Bobcat sub-compact tractors feature a tight turning radius – as little as 8.3 feet – so you can move in close to trees, buildings and other obstacles.

MID-PTO

Enjoy superior maneuverability for mowing around trees, buildings and other obstacles with a 2,200-rpm mid-PTO and mid-mount mower. With a mid-PTO, you have the option of combining two tools on one machine – one in the back and either one in the front or a mid-mount mower.

INTUITIVE CONTROL LEVERS

Great controls make it easier and more enjoyable to do more with your sub-compact tractor. You can match torque to the task with the HST range lever, moving effortlessly between high and low ranges. You can also adjust the mid-mount mower cutting height via a simple lever control. Rear and mid-PTO levers enable you to engage or disengage the PTOs separately or together.

| Model | CT1021 | CT1025 |
|---|-----------------------------------|-----------------------------------|
| Engine | Diesel | Diesel |
| Gross Horsepower | 21.0 hp (15.7 kW) | 24.5 hp (18.3 kW) |
| No. of Cylinders | 3 | 3 |
| Total Displacement | 61.4 cu. in. (1.0 L) | 61.4 cu. in. (1.0 L) |
| Fuel Tank Capacity | 6.7 gal. (25.5 L) | 6.7 gal. (25.5 L) |
| 3-Point, PTO & Hydraulics | | |
| 3-Point Hitch | Category 1 Limited | Category 1 Limited |
| 3-Point Lift Capacity* | 700 lb. (318 kg) | 700 lb. (318 kg) |
| 3-Point Link Stabilizers | Turnbuckle | Turnbuckle |
| Lift Control Type | Hydraulic Position Control System | Hydraulic Position Control System |
| Lifting Rod | Turnbuckle | Turnbuckle |
| Lower Links | Rigid | Rigid |
| Mid-PTO | Standard: 2200 rpm | Standard: 2200 rpm |
| PTO Horsepower | 16.3 hp (12.1 kW) | 18.8 hp (14.0 kW) |
| Rear Hydraulics (optional) | 1 Pair | 1 Pair |
| Rear PTO | 540 rpm | 540 rpm |
| Rear PTO System | Independent | Independent |
| Total Hydraulic Pump Capacity | 7.2 gpm (27.4 L/min.) | 7.2 gpm (27.4 L/min.) |
| Drive System | | |
| Transmission | 2-Range HST | 2-Range HST |
| Brakes | Wet Multi-Disc | Wet Multi-Disc |
| Rear Differential Lock | Std | Std |
| Four-Wheel Drive | Std | Std |
| Travel Speeds (w/ Ind. Tires) | | |
| Forward | 11.1 mph (17.8 km/hr.) | 11.1 mph (17.8 km/hr.) |
| Reverse | 7.6 mph (12.2 km/hr.) | 7.6 mph (12.2 km/hr.) |
| Dimensions | | |
| Overall Length (w/ 3 pt.) | 99.3 in. (2522 mm) | 99.3 in. (2522 mm) |
| Overall Width (w/ industrial tires) | 46.0 in. (1161 mm) | 46.0 in. (1161 mm) |
| Overall Height | 87.6 in. (2225 mm) | 87.6 in. (2225 mm) |
| Wheelbase | 55.1 in. (1400 mm) | 55.1 in. (1400 mm) |
| Ground Clearance | 6.3 in. (160 mm) | 6.3 in. (160 mm) |
| Weight | 1521 lb. (690 kg) | 1521 lb. (690 kg) |
| Steering | | |
| | Hydrostatic Power Steering | Hydrostatic Power Steering |
| Inside Turning Radius | 100.0 in. (2540 mm) | 100.0 in. (2540 mm) |
| Tilt Steering Wheel | — | — |
| Safety Equipment | | |
| Safety Interlock System (neutral start-operating) | Std | Std |
| Fold-Down ROPS (roll-over protective structure) | Std | Std |
| Fully Retractable Seat Belt | Std | Std |
| Features | | |
| Adjustable Seat | Std | Std |
| Cup Holder | Std | Std |
| Glow Plug Engine Preheat | Std | Std |
| Toolbox | Std | Std |
| Head Lights/Tail Lights/ Brake Lights | Std | Std |
| Cruise Control | Opt | Opt |
| Spark Arrestor Muffler | Opt | Opt |
| Horn/Hazard Flasher/Turn Signals | Std | Std |
| Rear Working Light | Opt | Opt |
| Side Mirror | — | — |
| Dealer-Installed Cab With Heat | Opt | Opt |

*Note: Hydraulic 3 pt. lift capacity will vary depending on lift point height.

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.

DOOSAN

Bobcat Company is a member of the Doosan Group. Doosan is a global leader in construction, grounds maintenance and material handling equipment, power and water solutions, and engineering that has proudly served customers and communities for more than a century. Bobcat®, the Bobcat logo and the colors of the Bobcat machine are registered trademarks of Bobcat Company in the United States and various other countries. ©2023 Bobcat Company. All rights reserved.

B-2275 (05/23)
EP-3M-0523-3650-F

Bobcat Company
250 East Beaton Drive • West Fargo, ND 58078
Bobcat.com



Bobcat®

One Tough Animal.