



Bobcat®

YOUR HEAVY-DUTY WORK COMPANION: 4000 PLATFORM COMPACT TRACTORS

For rugged power and work efficiency that quickly conquers mowing, overgrown fields, snow clearing, or driveway and private road maintenance, look to the Bobcat® 4000 platform compact tractors. These economical tractors have high horsepower, extra weight and your choice of two transmission types for performance that's matched to your property. The open cab is great for operators who frequently get on and off the tractor.



MANUAL SYNCHRO SHUTTLE TRANSMISSION OR HYDROSTATIC TRANSMISSION (3-RANGE HST)

Manual synchro shuttle transmission is similar to a stick-shift automobile, allowing you to clutch and shift across eight forward and eight rear speeds as you travel. Operators who prefer a manual transmission find it easy to use, and it provides great performance when moving up and down fields or traveling longer distances in one direction.

For maximum ease of use and fast, simple direction changes, choose the hydrostatic (HST) transmission. It is extremely effective for frequent front-end loader work, mowing or maneuvering in wooded areas while clearing brush. Instead of gears, a hydrostatic transmission uses hydraulic pressure to change your speed and range. You only need to stop moving if you want to change your range.

LINKED PEDAL LEVER OPTION

Increase engine rpm as you engage the travel pedal for operation that feels similar to driving a car. It enhances ease of use for front-end loader work and a variety of other jobs.

PTO CRUISE

Enables you to maintain the PTO rpm at your preferred setting – even as the tractor's load conditions change.

LEVER-CONTROLLED 3-POINT HITCH HEIGHT

Raise and lower lift arms from your seat with a remote lever in the cab.

Model	CT4045 HST	CT4045 SST	CT4050 HST	CT4050 SST	CT4055 SST	CT4058 HST
Engine	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel
Gross Horsepower	44.9 hp (33.5 kW)	44.9 hp (33.5 kW)	50.3 hp (37.3 kW)	50.3 hp (37.3 kW)	55.0 hp (41.0 kW)	57.7 hp (43.0 kW)
No. of Cylinders	3	3	3	3	3	3
Total Displacement	111.4 cu. in. (1.8 L)					
Fuel Tank Capacity	12.7 gal. (48.0 L)	11.9 gal. (45.0 L)	12.7 gal. (48.0 L)	11.9 gal. (45.0 L)	11.9 gal. (45.0 L)	12.7 gal. (48.0 L)
3-Point, PTO & Hydraulics						
3-Point Hitch	Category 1					
3-Point Lift Capacity*	2716 lb. (1232 kg)					
3-Point Link Stabilizers	Turnbuckle	Turnbuckle	Turnbuckle	Turnbuckle	Turnbuckle	Turnbuckle
Lift Control Type	Hydraulic Position Control System					
Lifting Rod	Turnbuckle	Turnbuckle	Turnbuckle	Turnbuckle	Turnbuckle	Turnbuckle
Lower Links	Rigid	Rigid	Rigid	Rigid	Rigid	Rigid
Mid-PTO	Optional: 2119 rpm	—	Optional: 2119 rpm	—	—	Optional: 2119 rpm
PTO Horsepower	32.8 hp (24.5 kW)	41.6 hp (31.0 kW)	39.3 hp (29.3 kW)	45.6 hp (34.0 kW)	49.6 hp (37.0 kW)	45.1 hp (33.7 kW)
Rear Hydraulics	1 Pair Std (2nd Pair Opt)	Opt 2 Pairs	1 Pair Std (2nd Pair Opt)	Opt 2 Pairs	Opt 2 Pairs	1 Pair Std (2nd Pair Opt)
Rear PTO	540 rpm					
Rear PTO System	Independent	Independent	Independent	Independent	Independent	Independent
Total Hydraulic Pump Capacity	16.5 gpm (62.4 L/min.)	14.1 gpm (53.4 L/min.)	16.5 gpm (62.4 L/min.)	16.5 gpm (62.4 L/min.)	14.1 gpm (53.4 L/min.)	16.5 gpm (62.5 L/min.)
Drive System						
Standard Transmission	3-Range HST	8F X 8R Synchro	3-Range HST	8F X 8R Synchro	8F X 8R Synchro	3-Range HST
Brakes	Wet Multi-Disc					
Rear Differential Lock	Std	Std	Std	Std	Std	Std
Four-Wheel Drive	Std	Std	Std	Std	Std	Std
Travel Speeds (w/ Ind. Tires)						
Forward	18.5 mph (29.7 km/hr.)	17.5 mph (28.2 km/hr.)	18.5 mph (29.7 km/hr.)	17.5 mph (28.2 km/hr.)	17.5 mph (28.2 km/hr.)	18.5 mph (29.7 km/hr.)
Reverse	12.9 mph (20.8 km/hr.)	17.1 mph (27.6 km/hr.)	12.9 mph (20.8 km/hr.)	17.1 mph (27.5 km/hr.)	17.1 mph (27.1 km/hr.)	12.9 mph (20.8 km/hr.)
Dimensions						
Overall Length (w/ 3 pt.)	125.5 in. (3189 mm)					
Overall Width (w/ industrial tires)	69.8 in. (1722 mm)					
Overall Height	97.4 in. (2473 mm)					
Wheelbase	71.2 in. (1810 mm)					
Ground Clearance (w/ industrial tires)	15.3 in. (387 mm)					
Weight	3745 lb. (1698 kg)					
Steering						
	Hydrostatic Power Steering					
Inside Turning Radius (w/ assisted braking)	103.5 in. (2630 mm)					
Tilt Steering Wheel	Std	Std	Std	Std	Std	Std
Safety Equipment						
Safety Interlock System (neutral start-operating)	Std	Std	Std	Std	Std	Std
Fold-Down ROPS (roll-over protective structure)	Std	Std	Std	Std	Std	Std
Fully Retractable Seat Belt	Std	Std	Std	Std	Std	Std
Features						
Adjustable Seat	Std	Std	Std	Std	Std	Std
Cup Holder	Std	Std	Std	Std	Std	Std
Glow Plug Engine Preheat	Std	Std	Std	Std	Std	Std
Toolbox	Std	Std	Std	Std	Std	Std
Head Lights/Tail Lights/ Brake Lights	Std	Std	Std	Std	Std	Std
Cruise Control	Opt	—	Opt	—	—	Opt
Spark Arrestor Muffler	Std	Std	Std	Std	Std	Std
Horn/Hazard Flasher/Turn Signals	Std	Std	Std	Std	Std	Std
Rear Working Light	Opt	Opt	Opt	Opt	Opt	Opt
Side Mirror	Opt	Opt	Opt	Opt	Opt	Opt
Enclosed Cab With Heat/AC	—	—	—	—	—	—

*Note: Hydraulic 3 pt. lift capacity will vary depending on lift point height.

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.

DOOSAN

Bobcat Company is a member of the Doosan Group. Doosan is a global leader in construction, grounds maintenance and material handling equipment, power and water solutions, and engineering that has proudly served customers and communities for more than a century. Bobcat®, the Bobcat logo and the colors of the Bobcat machine are registered trademarks of Bobcat Company in the United States and various other countries. ©2023 Bobcat Company. All rights reserved.

B-2277 (05/23)
EP-3M-0523-3650-F

Bobcat Company
250 East Beaton Drive • West Fargo, ND 58078
Bobcat.com



Bobcat®

One Tough Animal.