



Bobcat®

TOP PERFORMANCE AND COMFORT FOR DIFFICULT WORK: 5000 PLATFORM COMPACT TRACTORS

With plenty of horsepower, intuitive operation and ergonomic controls, 5000 platform tractors are built to take on a full day of tough groundskeeping tasks, from mowing to brush clearing and beyond. Excellent ground engagement – and a premium 3-point hitch – is essential for owners who need to use a variety of different implements, such as discs, cultivators and plows. A factory-installed deluxe cab allows you to work in maximum comfort, whether it's freezing and windy or humid and hot outdoors.



ENCLOSED, RADIO-READY CAB WITH HEAT AND AIR CONDITIONING

When the weather won't cooperate, a comfortable cab protects your comfort and your ability to get the job done. Get the ultimate in compact tractor comfort with panoramic visibility, a cab-integrated joystick for a front-end loader and other great features.

ELECTRONIC HYDROSTATIC TRANSMISSION (E-HST)

E-HST provides impressive ease of direction change and accelerates with near-effortless pressure on the travel pedal. It also enables true cruise control that keeps you moving at a constant speed. Even when you drive up a slope, there's no need to adjust the travel pedal to keep your momentum.

PTO CRUISE

Enables you to maintain the PTO rpm at your preferred setting – even as the tractor's load conditions change.

ELECTRONIC LINKED PEDAL

Enable your travel pedals to increase or decrease the engine rpm to make front-end loader work and other tasks even easier.

CRANK STYLE LIFT ROD ADJUSTMENT

Quickly move your links up and down – with the least amount of effort – while changing your implement.

LEVER-CONTROLLED 3-POINT HITCH HEIGHT

Raise and lower lift arms from your seat with a remote lever in the cab.

Model	CT5545 E-HST	CT5550 E-HST	CT5555 E-HST	CT5558 E-HST
Engine	Diesel	Diesel	Diesel	Diesel
Gross Horsepower	45.0 hp (33.5 kW)	50.0 hp (37.5 kW)	55.0 hp (41.0 kW)	57.7 hp (43.0 kW)
No. of Cylinders	3	3	3	3
Total Displacement	111.4 cu. in. (1.8 L)			
Fuel Tank Capacity	14.8 gal. (56.0 L)			
3-Point, PTO & Hydraulics				
3-Point Hitch	Category 1	Category 1	Category 1	Category 1
3-Point Lift Capacity*	3177 lb. (1441 kg)			
3-Point Link Stabilizers	Telescopic	Telescopic	Telescopic	Telescopic
Lift Control Type	Position With Draft Control			
Lifting Rod	Crank	Crank	Crank	Crank
Lower Links	Telescopic	Telescopic	Telescopic	Telescopic
Mid-PTO	Optional: 2103 rpm	Optional: 2103 rpm	Optional: 2103 rpm	Optional: 2103 rpm
PTO Horsepower	33.9 hp (25.3 kW)	38.9 hp (29.0 kW)	43.1 hp (32.1 kW)	48.3 hp (36.0 kW)
Rear Hydraulics	1 Pair Std (2nd and 3rd Opt)			
Rear PTO	540 rpm	540 rpm	540 rpm	540 rpm
Rear PTO System	Independent	Independent	Independent	Independent
Total Hydraulic Pump Capacity	17.8 gpm (67.6 L/min.)			
Drive System				
Standard Transmission	3-Range E-HST	3-Range E-HST	3-Range E-HST	3-Range E-HST
Brakes	Wet Multi-Disc	Wet Multi-Disc	Wet Multi-Disc	Wet Multi-Disc
Rear Differential Lock	Std	Std	Std	Std
Four-Wheel Drive	Std	Std	Std	Std
Travel Speeds (with ind. tires)				
Forward	17.5 mph (28.2 km/hr.)	17.5 mph (28.2 km/hr.)	17.5 mph (28.2 km/hr.)	17.5 mph (28.2 km/hr.)
Reverse	17.5 mph (28.2 km/hr.)	17.5 mph (28.2 km/hr.)	17.5 mph (28.2 km/hr.)	17.5 mph (28.2 km/hr.)
Dimensions				
Overall Length (w/ 3 pt.)	139.6 in. (3547 mm)			
Overall Width (w/ industrial tires)	74.2 in. (1885 mm)			
Overall Height	94.2 in. (2393 mm)			
Wheelbase	75.6 in. (1920 mm)			
Ground Clearance (w/ industrial tires)	13.0 in. (330 mm)			
Weight	4685 lb. (2125 kg)			
Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering
Inside Turning Radius (w/ assisted braking)	117.6 in. (2990 mm)			
Tilt Steering Wheel	Std	Std	Std	Std
Safety Equipment				
Safety Interlock System (neutral start-operating)	Std	Std	Std	Std
Fold-Down ROPS (roll-over protective structure)	—	—	—	—
Fully Retractable Seatbelt	Std	Std	Std	Std
Features				
Adjustable Seat	Std	Std	Std	Std
Cup Holder	Std	Std	Std	Std
Glow Plug Engine Preheat	Std	Std	Std	Std
Toolbox	Std	Std	Std	Std
Head Lights/Tail Lights/ Brake Lights	Std	Std	Std	Std
Cruise Control	Std	Std	Std	Std
Spark Arrestor Muffler	Std	Std	Std	Std
Horn/Hazard Flasher/Turn Signals	Std	Std	Std	Std
Rear Working Light	Std	Std	Std	Std
Side Mirror	Std	Std	Std	Std
Enclosed Cab With Heat/AC	Std	Std	Std	Std

*Note: Hydraulic 3 pt. lift capacity will vary depending on lift point height.

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.

DOOSAN

Bobcat Company is a member of the Doosan Group. Doosan is a global leader in construction, grounds maintenance and material handling equipment, power and water solutions, and engineering that has proudly served customers and communities for more than a century. Bobcat®, the Bobcat logo and the colors of the Bobcat machine are registered trademarks of Bobcat Company in the United States and various other countries. ©2023 Bobcat Company. All rights reserved.

B-2278 (05/23)
EP-3M-0523-3650-F

Bobcat Company
250 East Beaton Drive • West Fargo, ND 58078
Bobcat.com



Bobcat®

One Tough Animal.