



Bobcat®

WIDE-RANGING PRODUCTIVITY. FULLY ENCLOSED COMFORT. BOBCAT UT6566 UTILITY TRACTOR

The Bobcat® UT6566 provides the power and capability you need to tackle jobs while staying comfortable and confident. This 66-horsepower utility tractor provides all the heavy-lifting performance you need for moving bigger loads and handling Category 2 3-point implements. Whether you're an experienced operator or a first-time tractor owner, you'll quickly move from task to task with intuitive, operator-friendly features that power an endless list of accomplishments.

COMFORTABLE ENCLOSED CAB WITH HEAT AND AIR CONDITIONING

Stay out of the elements and surround yourself in comfort with the fully enclosed cab. The UT6566 cab is also radio-ready. Controls, gauges and buttons are thoughtfully laid out – easy to find and use. An illuminated dashboard helps you operate and monitor performance when natural light levels are low.



LED WORK LIGHTS

Bright LED headlights illuminate the job for evening work and other low-light conditions. Additional LED work lights on the front and rear provide extra illumination and visibility for the job.

MECHANICAL SELF-LEVELING LOADER

The standard mechanical self-leveling loader automatically keeps your load level throughout its full range of loader motion. Its ease of operation is ideal for keeping a level bucket or pallet fork and minimizing spillage. The front-end loader is easy to hook up and remove, saving you installation time.

POWERSHUTTLE TRANSMISSION

The UT6566 features a 12x12 powershuttle transmission that has three ranges. Each range offers four powerful gears in both forward and reverse. With your electronic hand clutch, you have smooth, easy shifting from gear to gear, giving you high torque or faster travel speeds on command.

REAR PTO AND CATEGORY 2 3-POINT HITCH

Equipped with the Category 2 3-point hitch, a 540 rpm PTO and a pair of rear remote hydraulics (plus the option to have a second or third), the UT6566 tractor is packed with major productivity potential. Use both non-powered and PTO-powered implements to take on an endless variety of tasks on your property or jobsite.

SPECIFICATIONS

Model	UT6566
Engine	
Emissions Tier (EPA)	Tier 4/Stage 5
Engine Make	Daedong
Engine Model	4HT-TP4A
Gross Horsepower	66.4 hp (49.5 kW)
No. of Cylinders	4
Total Displacement	148.6 cu. in. (2435 cc)
Fuel Tank Capacity	25.1 gal. (95.0 L)
RPM	2600
3-Point, PTO & Hydraulics	
3-Point Hitch	Category 2
3-Point Lift Capacity*	3898 lb. (1768 kg)
Lift Control Type	Position With Draft Control
Mid-PTO	—
PTO Horsepower	51.1 hp (38.1 kW)
Rear PTO	540/540E rpm
Rear PTO System	Independent
Total Hydraulic Pump Capacity	19.2 gpm (72.7 L/min.)
Implement Hydraulic Flow	10.9 gpm (41.6 L/min.)
Steering Hydraulic Flow	8.2 gpm (31.1 L/min.)
Drive System	
Standard Transmission	3-Range Powershuttle With Electronic Clutch
Brakes	Wet Multi-Disc
Four-Wheel Drive	Std
Number of Forward Speeds	4
Travel Speeds	
Forward	19.8 mph (31.8 km/hr.)
Reverse	19.5 mph (31.3 km/hr.)



Model	UT6566
Dimensions	
Length	148.8 in. (3779 mm)
Width	77.2 in. (1960 mm)
Height	99.3 in. (2522 mm)
Wheelbase	82.7 in. (2100 mm)
Ground Clearance	12.3 in. (312 mm)
Weight	5830 lb. (2644 kg)
Front Tire Size	Front Industrial (Ag, Multi-Use) 12.5/80-18 (9.5-24, 340/80R18)
Rear Tire Size	Rear Industrial (Ag, Multi-Use) 18.4-24 (16.9-30, 480/80R26)
Steering	
Turning Radius	147.0 in. (3733 mm)
Outside Turning Diameter	307.0 in. (7797 mm)
Tilt Steering Wheel	Std
Safety Equipment	
Fold-Down ROPS (roll-over protective structure)	—
Features	
Suspension Seat	Std
Glow Plug Engine Preheat	Std
Cruise Control	Std
Spark Arrestor Muffler	Std
Horn	Std
Loader Attachment	
Loader Model	FL10
Loader Lift Height	129.0 in. (3276 mm)
Lift Capacity at Bucket Pivot	3017 lb. (1368 kg)
Bucket Width	81.0 in. (2057 mm)
Loader Control Valve and Joystick	Std

*At 24 inches behind lift point.

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.

DOOSAN

Bobcat Company is a member of the Doosan Group. Doosan is a global leader in construction, grounds maintenance and material handling equipment, power and water solutions, and engineering that has proudly served customers and communities for more than a century. Bobcat®, the Bobcat logo and the colors of the Bobcat machine are registered trademarks of Bobcat Company in the United States and various other countries. ©2024 Bobcat Company. All rights reserved.



B-3026 (05/24)
EP-XX-0524-13840-F

Bobcat Company
250 East Beaton Drive • West Fargo, ND 58078
Bobcat.com



Bobcat®

One Tough Animal.