



Bobcat

Connected with Machine IQ telematics.



CLASSIC LOADERS: RELIABILITY AND VALUE FOR EVERY JOB

Compact Track Loaders: T450 | T595 | T650 | T770

Skid-Steer Loaders: S70 | S450 | S590 | S650 | S770

PROVEN PERFORMANCE. FAMILIAR CONTROL. SIMPLIFIED CHOICES.

Bobcat® Classic loaders deliver the straightforward performance, unbeatable reliability and legendary control operators have relied on for decades. Now with refreshed styling, modern essentials and simplified package options, it's easier than ever to own a Bobcat loader.



SIMPLIFIED PACKAGES

The Classic lineup features four streamlined package options — Work, Core, Comfort and Comfort Plus* — making it easy to choose the right machine for the job and budget.

COMPETITIVE PRICING

Designed with value in mind, Classic loaders offer a competitive price point and lower total cost of ownership, making professional-grade performance more accessible across a wide range of applications.

LEGENDARY CONTROL

Classic loaders deliver the smooth handling and familiar Bobcat response operators have trusted for decades. Choose industry-defining hand/foot controls or selectable joystick controls for confident operation.

UPDATED OPERATOR EXPERIENCE

The cab enhances usability and jobsite awareness with an upgraded deluxe display featuring an integrated rear camera* for added operator awareness.

*Comfort Plus package with integrated rear camera coming summer 2026.



COMPACT TRACK LOADERS

		T450	T595	T650	T770
PERFORMANCE	Rated Operating Capacity (ROC) (35% of tipping load)	1490 lb. (676 kg)	2100 lb. (953 kg)	2500 lb. (1134 kg)	3475 lb. (1576 kg)
	Tipping Load	4257 lb. (1931 kg)	6000 lb. (2721 kg)	7143 lb. (3240 kg)	9929 lb. (4504 kg)
	Height to Bucket Hinge Pin	109.5 in. (2781 mm)	119.0 in. (3023 mm)	124.0 in. (3149 mm)	132.0 in. (3353 mm)
	Lift Arm Path	Radius	Vertical	Vertical	Vertical
SIZE AND SPEED	Operating Weight	6424 lb. (2914 kg)	7906 lb. (3586 kg)	8980 lb. (4073 kg)	10,515 lb. (4770 kg)
	Width With Bucket	56.0 in. (1422 mm)	68.0 in. (1727 mm)	74.0 in. (1880 mm)	80.0 in. (2032 mm)
	Height With Cab	77.8 in. (1976 mm)	77.6 in. (1971 mm)	81.3 in. (2065 mm)	81.3 in. (2065 mm)
	Travel Speed – Low Range	7.0 mph (11.3 km/hr.)	7.1 mph (11.4 km/hr.)	6.0 mph (9.7 km/hr.)	6.6 mph (10.6 km/hr.)
	Travel Speed – High Range (Two-Speed travel)	11.0 mph (17.7 km/hr.)	10.4 mph (16.7 km/hr.)	8.7 mph (14.0 km/hr.)	10.7 mph (17.2 km/hr.)
ENGINE	Emissions Tier (EPA)	Tier 4	Tier 4	Tier 4	Tier 4
	Engine Power	55.0 hp (41.0 kW)	70.0 hp (52.2 kW)	74.0 hp (55.2 kW)	92.0 hp (68.6 kW)
	Type	Turbo Diesel	Turbo Diesel	Turbo Diesel	Turbo Diesel
	Fuel Tank Capacity	17.1 gal. (64.9 L)	36.5 gal. (138.2 L)	43.8 gal. (165.8 L)	43.8 gal. (165.8 L)
	Horsepower Management	Included With SJC Option	Included With SJC Option	Included With SJC Option	Included With SJC Option
TRACKS/ UNDERCARRIAGE	Track Width – Standard	11.8 in. (300 mm)	12.6 in. (320 mm)	12.6 in. (320 mm)	17.7 in. (450 mm)
	Track Width – Optional	–	–	17.7 in. (450 mm)	17.7 in. (450 mm)
	Ground Pressure (with standard tracks)	4.8 psi (0.33 bar)	5.1 psi (0.35 bar)	5.7 psi (0.39 bar)	4.2 psi (0.29 bar)
	Length of Track on Ground	50.2 in. (1275 mm)	54.1 in. (1374 mm)	58.5 in. (1485 mm)	63.7 in. (1618 mm)
AUXILIARY HYDRAULICS	Hydraulic System Pressure (Standard and High Flow)	3300 psi (22.8 MPa)	3500 psi (24.1 MPa)	3500 psi (24.1 MPa)	3500 psi (24.1 MPa)
	Hydraulic Standard Flow	16.7 gpm (63.2 L/min.)	17.1 gpm (64.7 L/min.)	23.0 gpm (87.1 L/min.)	23.0 gpm (87.1 L/min.)
	Hydraulic High Flow	–	26.7 gpm (101.1 L/min.)*	30.5 gpm (115.5 L/min.)*	36.6 gpm (138.5 L/min.)*

SKID-STEER LOADERS

		S70	S450	S590	S650	S770
PERFORMANCE	Rated Operating Capacity (ROC) (50% of tipping load)	760 lb. (344 kg)	1370 lb. (621 kg)	2000 lb. (907 kg)	2690 lb. (1220 kg)	3350 lb. (1520 kg)
	Tipping Load	1520 lb. (689 kg)	2740 lb. (1243 kg)	4000 lb. (1814 kg)	5380 lb. (2440 kg)	6700 lb. (3039 kg)
	Height to Bucket Hinge Pin	94.5 in. (2400 mm)	109.5 in. (2781 mm)	119.0 in. (3023 mm)	124.0 in. (3149 mm)	132.0 in. (3353 mm)
	Lift Arm Path	Radius	Radius	Vertical	Vertical	Vertical
SIZE AND SPEED	Operating Weight	2892 lb. (1312 kg)	5370 lb. (2436 kg)	6649 lb. (3016 kg)	7901 lb. (3584 kg)	9154 lb. (4152 kg)
	Width With Bucket	35.5 in. (902 mm)	62.0 in. (1575 mm)	68.0 in. (1727 mm)	74.0 in. (1880 mm)	74.0 in. (1880 mm)
	Height With Cab	71.4 in. (1814 mm)	77.8 in. (1976 mm)	77.6 in. (1971 mm)	81.3 in. (2065 mm)	81.3 in. (2065 mm)
	Travel Speed – Low Range	6.3 mph (10.1 km/hr.)	7.6 mph (12.3 km/hr.)	7.3 mph (11.7 km/hr.)	7.1 mph (11.4 km/hr.)	7.1 mph (11.4 km/hr.)
	Travel Speed – High Range (Two-Speed travel)	–	9.2 mph (14.8 km/hr.)	11.7 mph (18.8 km/hr.)	12.3 mph (19.7 km/hr.)	12.3 mph (19.8 km/hr.)
ENGINE	Emissions Tier (EPA)	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4
	Engine Power	23.5 hp (17.5 kW)	49.0 hp (36.5 kW)	68.0 hp (50.7 kW)	74.0 hp (55.2 kW)	92.0 hp (68.6 kW)
	Type	Diesel	Turbo Diesel	Turbo Diesel	Turbo Diesel	Turbo Diesel
	Fuel Tank Capacity	6.5 gal. (24.6 L)	14.2 gal. (53.8 L)	24.8 gal. (93.7 L)	23.9 gal. (90.5 L)	23.9 gal. (90.5 L)
	Horsepower Management	–	Included With SJC Option	Included With SJC Option	Included With SJC Option	Included With SJC Option
TIRES	Bobcat Heavy Duty	Opt	Std	Std	Std	Std
	Bobcat Standard	Std	–	–	–	–
AUXILIARY HYDRAULICS	Hydraulic System Pressure (Standard and High Flow)	2000 psi (13.8 MPa)	3300 psi (22.8 MPa)	3500 psi (24.1 MPa)	3500 psi (24.1 MPa)	3500 psi (24.1 MPa)
	Hydraulic Standard Flow	8.9 gpm (33.7 L/min.)	16.7 gpm (63.2 L/min.)	17.1 gpm (64.7 L/min.)	23.0 gpm (87.1 L/min.)	23.0 gpm (87.1 L/min.)
	Hydraulic High Flow	–	–	26.7 gpm (101.1 L/min.)*	30.5 gpm (115.5 L/min.)*	36.6 gpm (138.5 L/min.)*

*Optional

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.



Bobcat Company is a member of the Doosan Group. Doosan is a global leader in construction, grounds maintenance and material handling equipment, power and water solutions, and engineering that has proudly served customers and communities for more than a century. Bobcat®, the Bobcat logo and the colors of the Bobcat machine are registered trademarks of Bobcat Company in the United States and various other countries. ©2026 Bobcat Company. All rights reserved.

DOOSAN